



CERTIFICATE

No. U6 107849 0009 Rev. 00

Holder of Certificate: Leding Light B.V.

Puntweg 11 3208LD Spijkenisse THE NETHÉRLANDS

Certification Mark:



Electronic controlgear for LED modules Product:

LED Driver

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704022033104-00

2020-09-08 Date,

(Yin Ji)



CERTIFICATE

No. U6 107849 0009 Rev. 00

Model(s): LU*100SF; LU*150SF; LU*200SF; LU*250SF; LU*300SF;

LU*350SF; LU*400SF; LU*450SF; LU*500SF; LU*600SF; LU*700SF; LU*750SF; LU*800SF; LU*900SF; LU*1000SF; LU*1100SF; LK*150SF; LK*200SF; LK*250SF; LK*300SF; LK*350SF; LK*400SF; LK*450SF; LK*500SF; LK*600SF; LK*700SF; LK*750SF; LK*800SF;

LK*900SF; LK*1000SF; LK*1100SF; LK*1200SF; LU*200-1200D A; LU*200-1200D B; LU*200-1200S A;

LU*200-1200S B.

Parameters:

Rated voltage: 220-240V~ Rated frequency: 50/60Hz

Rated Output: Refer to model list

Uout: 50VDC Protection Class: II

ta: -20 ~ +40°C

tc: 90°C Protection against electric shock: SELV

Type of Output: Constant current type

Install Classification: Independent

. independent				
Model	Output voltage (Vd.c.)	Irated (mA)	Prated (W)	
LU*100SF	30-40	100	4.3	
LU*150SF	30-40	150	6.5	
LU*200SF	30-40	200	8.7	
LU*250SF	30-40	250	10.8	
LU*300SF	30-40	300	13.0	
LU*350SF	30-40	350	15.2	
LU*400SF	30-40	400	17.3	
LU*450SF	30-40	450	19.5	
LU*500SF	30-40	500	21.7	
LU*600SF	30-40	600	26.0	
LU*700SF	30-40	700	30.3	
LU*750SF	30-40	750	32.5	
LU*800SF	30-40	800	34.7	
LU*900SF	30-40	900	39.0	
LU*1000SF	30-40	1000	43.3	
LU*1100SF	30-40	1100	47.7	
LU*1200SF	30-40	1200	52.0	
LK*100SF	30-40	100	4.3	
LK*150SF	30-40	150	6.5	
LK*200SF	30-40	200	8.7	
LK*250SF	30-40	250	10.8	
LK*300SF	30-40	300	13.0	
LK*350SF	30-40	350	15.2	
LK*400SF	30-40	400	17.3	
LK*450SF	30-40	450	19.5	
LK*500SF	30-40	500	21.7	
LK*600SF	30-40	600	26.0	



CERTIFICATE

No. U6 107849 0009 Rev. 00

LK*700SF	30-40	700	30.3
LK*750SF	30-40	750	32.5
LK*800SF	30-40	800	34.7
LK*900SF	30-40	900	39.0
LK*1000SF	30-40	1000	43.3
LK*1100SF	30-40	1100	47.7
LK*1200SF	30-40	1200	52.0
LU*200-1200D A	20-40	100-1200	Max. 50
LU*200-1200D B	20-40	100-1200	Max. 50
LU*200-1200S A	20-40	100-1200	Max. 50
LU*200-1200S B	20-40	100-1200	Max. 50

Tested EN 61347-1:2015

according to: EN 61347-2-13:2014/A1:2017 EN 62384:2006/A1:2009

Production 105512

Facility(ies):